

References



I SSL LED DIM0-10V



I SSL LED DIMBT

Certificates



Class I

120V - 277V

Wood shade colors

- 20 Ivory White
- 21 Natural Cherry
- 22 Natural Beech
- 24 Yellow
- 25 Orange
- 26 Red
- 28 Blue
- 29 Grey
- 30 Turquoise
- 31 Chocolate



Components



**Top diffuser**  
Black or White

The standard top diffuser is white. Black is also available if you want no upward light diffusion.

**Bottom diffuser**  
Matt satin acrylic



**Metal canopy**  
Brushed Nickel  
50 x 11,5 x 5 cm

**Electrical cable**  
Transparent 2 m drop



**Steel cable**  
2 x 2 m drop



**LED**

**Linear Module**  
5 x 5,5 W 350 mA

**Energy class**


A+  
LED integrated  
Not replaceable



**Driver**

MEANWELL  
1 unit - Ref. NPF 40D-24  
+  
Bluetooth Control - CASAMBI  
1 unit - Ref. CBU - ASD

Driver housed in canopy.



Details

Input Voltage	Luminous Flux *	CRI	Watt.	CCT	Lifetime (L70)
120V-277V	2040 lm	90	30 W	3000 °K	40000h

\* Measurements taken using white shades, Veneer Ref: 20 Ivory White

