## leolux LX

### LX682 Design: Frans Schrofer, 2017



#### Technical details

<u>Model</u>

Inner frame Springs Wadding <u>Legs</u>	Sheet material Elastic belts HR foam 50kg/m³, wadding: Leoskin HR foam 30kg/m³, wadding: Leoskin Polyether foam 30kg/m³, wadding: Leoskin
Foot Legs Gliders	Steel, in all standard epoxy colours (powder coating) Polished aluminium, in all standard epoxy colours (powder coating) Felt, gray
<u>Upholstery</u>	
Upholstery Stitching Decorative stitch	Fabric or leather Colour-to-colour or one of the standard colours. Flat seam, double stitch seam and Artisan seam
Exception	We do not recommend upholstery in patterned fabrics because of design and seam format
<u>Functions</u>	
Swivel	Fitted with auto return mechanism
<u>Comments</u>	
Deviating stitching	When opting for contrast stitching, this option applies to the entire item. If the inside and outside are selected with two different deviating stitching colours, this must be explicitly stated on the order. Deviating stitching is not possible on the decorative stitch Artisan, it is always the same colour of stitching as the outside.
Certifications	All sheet materials used in this model comply with the CARB2 requirement or are NAF certified
	On request foam materials with additional flame retardants can be applied.

### Technical drawings

# leolux LX

