

SMALL SUSPENSION / **Saturnia LED**
by Oskar Cerezo

References



SAT SP LED DIM0-10V



SAT SP LED DIMBT

Certificates



Class I

120V - 277V

Wood shade colors

- 20 Ivory White
- 21 Natural Cherry
- 22 Natural Beech
- 24 Yellow
- 25 Orange
- 26 Red
- 28 Blue
- 29 Grey
- 30 Turquoise
- 31 Chocolate



Components



Top diffuser

Black or White

The standard top diffuser is white. Black is also available if you want no upward light diffusion.

Bottom diffuser

Matt satin acrylic



Metal canopy

Brushed Nickel
ø 23 cm


Electrical cable

Transparent 2 m drop



Steel cable

3 x 2 m drop



LED

Linear Module
4 x 5,5 W 350 mA

Energy class


A+
LED integrated
Not replaceable



Driver

MEANWELL
1 unit - Ref. LPF 25D-36
+
Bluetooth Control - CASAMBI
1 unit - Ref. CBU - ASD

Driver housed in canopy.



Details

Input Voltage	Luminous Flux *	CRI	Watt.	CCT	Lifetime (L70)
120V-277V	1866 lm	90	25 W	3000 °K	40000h

* Measurements taken using white shades, Veneer Ref: 20 Ivory White

