

24 Yellow

25 Orange 26 Red 28 Blue 29 Grey 30 Turquoise 31 Chocolate

LED X-Club / MEDIUM SUSPENSION


by Burkhard Dämmer



References	Certificates	Wood shade colors		
X SM LED DIMO-10V	C€	20 Ivory White 21 Natural Cherry		
	Class I	22 Natural Beech		

X SM LED DIMBT 120V - 277V

Components





Top diffuser

Black or White

The standard top diffuser is white. Black is also available if you want no upward light diffusion.

Bottom diffuser

Matt satin acrylic



Metal canopy

Brushed Nickel 50 x 11,5 x 5 cm

Electrical cable

Transparent 2 m drop



Steel cable

4 x 2 m drop



LED

Energy class

LED integrated

Not replaceable

Linear Module 4 x 8,1 W 700 mA



Driver

MEANWELL 1 unit - Ref. NPF 40D-30

Bluetooth Control - CASAMBI 1 unit - Ref. CBU - ASD

Driver housed in canopy.



75

Details

	nput oltage	Luminous Flux *	CRI	Watt.	ССТ	Lifetime (L70)
1	20V-277V	2832 lm	90	35 W	3000 °K	40000h

^{*} Measurements taken using white shades, Veneer Ref: 20 Ivory White